

Distortion Rate For Tail Print Plates For .067 Is 97.61%



Custom Bistro
10 x 6 3/4 x 12

DATE: 2/10/16

SCALE: FULL

This .020" Microdot Is For Flexographic Printing Only.
It Should Be Placed On Every Color At The
Center Of Largest Copy (Top To Bottom). The Left Microdot
Gets Placed 1/64" Inside The Paste Area.
The Right Microdot Gets Placed 1/64" Outside
The Right Side Back Fold Edge Line.


BORDER DESIGNS
Because Of Machine Movement In Bag Conversion, Copy Should Be Placed At Least 1/4" From Fold Lines Or Edges.
In The Top Area, Use 1/2" Bleed.
Border Designs Should Be Kept 1/2" From Fold Edges, Top Cutoff And Bottom Fold.

PLEASE NOTE: All Screen, Half-Tones And Process Jobs Must Be Reviewed By Duro's Graphic Printing Division Before Preparing Art.


**This Proof is For Copy,
Elements And Position Only.
NOT FOR COLOR APPROVAL.**

Fill All 5 Anti-Bounce Area With
40% Screen In All Colors
Containing Screens


Full Panel Print
Must Bleed Into
Top & Bottom Panel Of Bag,
Which Is Indicated On Template



Anti-Bounce Strips



Fold And
Paste Lines



Clone
Areas



Lines



Center
Lines

